Backuppc auf Centos mit LDAP

Hauseigenes Apt-Repo: https://apt.iteas.at

Verwendetes System: CentOS 7

Installation

```
yum install perl-LDAP.noarch perl-Apache-Session-LDAP.noarch httpd mod_perl
backuppc elinks bzip2 zsh cifs-utils nload
usermod -s /bin/zsh backuppc
```

Konfiguration

Ändern der Config:

```
nano /etc/BackupPC/config.pl
```

config.pl

```
# von

$Conf{CgiAdminUserGroup} = '';
 $Conf{CgiAdminUsers} = '';

# auf

$Conf{CgiAdminUserGroup} = '';
 $Conf{CgiAdminUsers} = 'backuppc';

# von

$Conf{PingPath} = '';

# zu

$Conf{PingPath} = '/bin/ping';
```

Apacheconfig für Backuppc editieren:

```
nano /etc/httpd/conf.d/BackupPC.conf
```

BackupPC.conf

```
<Directory /usr/share/BackupPC/>
 # BackupPC requires valid authentication in order for the web
interface to
 # function properly. One can view the web interface without
authentication
 # though all functionality is disabled.
 #
 # htpasswd -c /etc/BackupPC/apache.users yourusername
 #
AuthType Basic
 AuthUserFile /etc/BackupPC/apache.users
 AuthName "BackupPC"
<IfModule mod_authz_core.c>
 <RequireAll>
 Require valid-user
 <RequireAny>
 Require local
 # --> In order to access only this specific IP
 # Require ip 192.168.16
 Require all granted
 </RequireAny>
 </RequireAll>
 </IfModule>
 <IfModule !mod_authz_core.c>
 AllowOverride All
 Order allow,deny
 #Deny from all
 Allow from all
 </IfModule>
</Directory>
Alias /BackupPC/images /usr/share/BackupPC/html/
 ScriptAlias /BackupPC /usr/share/BackupPC/sbin/BackupPC_Admin
 ScriptAlias /backuppc /usr/share/BackupPC/sbin/BackupPC_Admin
```

```
chown -R backuppc:backuppc /var/lib/BackupPC
```

Benutzer anlegen

```
htpasswd -c /etc/BackupPC/apache.users backuppc
setcap cap_net_raw+ep /bin/ping
systemctl restart backuppc.service
systemctl restart httpd.service
```

Migration von Ubuntu auf Centos7

Folgende Dinge müssen beim Migrieren geändert/angepasst werden:

- Konfigfiles der einzelnen Hosts liegen nicht unter `/etc/backuppc` sonder unter `/etc/BackupPC/pc`. Bei Ubuntu ist das ein symbolischer Link.
- Configfiles müssen die Gruppe „apache“ verwenden (Syntax bleibt gleich)
- Das Hauptverzeichnis von Backuppc ist in CentOS7 `/var/lib/BackupPC` und nicht wie in Ubuntu `/var/lib/backuppc`.
- SSH-Keys natürlich nicht vergessen zu kopieren.

From:
https://deepdoc.at/dokuwiki/ - **DEEPDOC.AT - enjoy your brain**

Permanent link:
https://deepdoc.at/dokuwiki/doku.php?id=server_und_serverdienste:backuppc_auf_centos_mit_ldap

Last update: **2021/03/04 15:25**